



TITLE
PW.1.5x1x1.IFB.DIV.AG

DRAWN BY **J. Ellison** DATE **07/02/2022**

CUSTOMER **CUSTOMER**

NOTE:
Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

ALL DIMENSIONS +/- 5mm
UNLESS OTHERWISE STATED

DESCRIPTION:
PW.1.5x1x1.IFB.DIV.AG Sectional cold water storage tank c/w raised float valve housing to provide an AG Air gap

A4

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
21/04/2021	A	FIRST ISSUE

TANK SPECIFICATION :

INTERNAL DIMENSIONS	1500 x 1000 x 1000mm
EXTERNAL DIMENSIONS	1640 x 1140 x 1201mm
NOM. CAPACITY	1500 Litres
INSULATION THICKNESS	25mm
MATERIAL	Hot press moulded GRP

TANKS DIRECT

SCALE:1:25 SHEET 1 OF 1