



TITLE
PW.1.5x1x1.5.IFB.AG

DRAWN BY J. Ellison DATE 04/02/2022

CUSTOMER CUSTOMER

NOTE:
Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

DESCRIPTION:
PW.1.5x1x1.5.IFB.AG Sectional cold water storage tank c/w access manways to provide an AG Air gap

A4 ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
25/01/2022	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1500 x 1000 x 1500mm
EXTERNAL DIMENSIONS	1660 x 1380 x 1701mm
NOM. CAPACITY	2250 Litres
INSULATION THICKNESS	25mm
MATERIAL	Hot press moulded GRP

TANKS DIRECT

SCALE:1:30 SHEET 1 OF 1