



Internal Division

**TANK SPECIFICATION :**

INTERNAL DIMENSIONS	2500 x 2000 x 1500mm
EXTERNAL DIMENSIONS	2660 x 2377 x 1707mm
NOM. CAPACITY	7500 Litres
INSULATION THICKNESS	25mm
MATERIAL	Hot press moulded GRP



TITLE  
**PW.2.5x2x1.5.IFB.DIV.AG**

DRAWN BY **J. Ellison** DATE **07/02/2022**

CUSTOMER  
**CUSTOMER**

**NOTE:**  
Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

ALL DIMENSIONS +/- 5mm  
UNLESS OTHERWISE STATED

DESCRIPTION:  
**PW.2.5x2x1.5.IFB.DIV.AG** Sectional cold water storage tank c/w access manways to provide an AG Air gap

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
18/05/2021	A	FIRST ISSUE