



TITLE
 PW.3x1x1.IFB.DIV.AB
 (1.5+1.5)

DRAWN BY J. Ellison **DATE** 07/02/2022

CUSTOMER CUSTOMER

NOTE:
 Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

ALL DIMENSIONS +/- 5mm
 UNLESS OTHERWISE STATED

DESCRIPTION:
 PW.3x1x1.IFB.DIV.AB. Sectional cold water storage tank c/w raised float valve housing to provide an AB Air gap

A4

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
18/11/2021	A	FIRST ISSUE

TANK SPECIFICATION :

INTERNAL DIMENSIONS	3000 x 1000 x 1000mm
EXTERNAL DIMENSIONS	3150 x 1140 x 1567mm
NOM. CAPACITY	3000 Litres
INSULATION THICKNESS	25mm
MATERIAL	Hot press moulded GRP

SCALE:1:35

SHEET 1 OF 1