



**TITLE**  
**PW.5x2x1.IFB.DIV.AB**  
**(2.5+2.5)**

**DRAWN BY** J. Ellison **DATE** 07/02/2022

**CUSTOMER** CUSTOMER

**NOTE:**  
 Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

ALL DIMENSIONS +/- 5mm  
 UNLESS OTHERWISE STATED

**DESCRIPTION:**  
 PW.5x2x1.IFB.DIV.AB Sectional cold water storage tank c/w raised float valve housing to provide an AB Air gap

A4

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
24/01/2022	A	FIRST ISSUE

**TANK SPECIFICATION :**

INTERNAL DIMENSIONS	5000 x 2000 x 1000mm
EXTERNAL DIMENSIONS	5140 x 2150 x 1567mm
NOM. CAPACITY	10,000 Litres
INSULATION THICKNESS	25mm
MATERIAL	Hot press moulded GRP

SCALE:1:50

SHEET 1 OF 1