



**TITLE**  
PW.1.5x1.5.IFB.DIV.AB  
OFFSET

DRAWN BY J. Ellison DATE 07/02/2022

CUSTOMER CUSTOMER

**NOTE:**  
Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

ALL DIMENSIONS +/- 5mm  
UNLESS OTHERWISE STATED

A4

**DESCRIPTION:**  
PW.1.5x1.5.IFB.DIV.AB Sectional cold water storage tank c/w raised float valve housing to provide an AB Air gap

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
25/01/2022	A	FIRST ISSUE

**TANK SPECIFICATION :**

INTERNAL DIMENSIONS	1500 x 1000 x 1500mm
EXTERNAL DIMENSIONS	1660 x 1160 x 2067mm
NOM. CAPACITY	2250 Litres
INSULATION THICKNESS	25mm
MATERIAL	Hot press moulded GRP



SCALE:1:35

SHEET 1 OF 1