



TITLE		NOTE: All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.	
PW338.INS (AG)			
DRAWN BY	J. Ellison	DATE	06/04/2022
CUSTOMER	CUSTOMER		

DESCRIPTION:	
PW338-AG One piece cold water storage tank suitable for AG/AF Air gaps	
A4	

ALL DIMENSIONS IN MM - DO NOT SCALE		
-------------------------------------	--	--

DATE	VERSION	NOTES
16/12/2021	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	610 x 610 x 910mm
EXTERNAL DIMENSIONS	805 x 805 x 1010mm
NOM. CAPACITY	338 Litres
DRY WEIGHT	25 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

	SCALE: 1:20	SHEET 1 OF 1
--	-------------	--------------