



TITLE	PW250.INS.AG	
DRAWN BY	C.MORRIS	DATE 28/11/2017
CUSTOMER	CUSTOMER	

NOTE	All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.	
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	A4	

DESCRIPTION:	PW250 one piece cold water storage tank suitable for AG/AF Air gap	
ALL DIMENSIONS IN MM - DO NOT SCALE		

DATE	VERSION	NOTES
04/10/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1000 x 500 x 500mm
EXTERNAL DIMENSIONS	1180 x 680 x 536mm
NOM. CAPACITY	250 Litres
DRY WEIGHT	20 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

	SCALE: 1:15	SHEET 1 OF 1
--	-------------	--------------