



3 No 40mm Encapsulated  
RHS Steel Bracings

TITLE <b>PW1050.INS (AG)</b>	
DRAWN BY J. Ellison	DATE 06/04/2022
CUSTOMER CUSTOMER	

<b>NOTE:</b> All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

<b>DESCRIPTION:</b> PW1050-AB One piece cold water storage tank suitable for AG/AF Air gaps
A4
ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
22/10/2019	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1500 x 500 x 1400mm
EXTERNAL DIMENSIONS	1665 x 665 x 1453mm
NOM. CAPACITY	1050 Litres
DRY WEIGHT	82 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

	SCALE: 1:20	SHEET 1 OF 1
--	-------------	--------------