



TITLE
PW225.INS.AB

DRAWN BY **C.MORRIS** DATE **28/11/2017**

CUSTOMER **CUSTOMER**

NOTE:
All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

DESCRIPTION:
PW225 One piece cold water storage tank c/w raised float valve housing to provide an AB Air gap

A4 ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
08/09/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	610 x 610 x 610mm
EXTERNAL DIMENSIONS	805 x 805 x 983mm
NOM. CAPACITY	225 Litres
DRY WEIGHT	18 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

TANKS DIRECT

SCALE: 1:15 SHEET 1 OF 1