



3 No 40mm Encapsulated  
RHS Steel Bracings

TITLE  
**PW1125.INS (AB)**

DRAWN BY J. Ellison DATE 06/04/2022

CUSTOMER CUSTOMER

**NOTE:**  
All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm  
UNLESS OTHERWISE STATED

DESCRIPTION:  
PW1125-AB One piece cold water storage tank suitable for AB Air gaps

A4 ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
22/10/2019	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1500 x 500 x 1500mm
EXTERNAL DIMENSIONS	1665 x 665 x 1815mm
NOM. CAPACITY	1125 Litres
DRY WEIGHT	90 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

**TANKS DIRECT**

SCALE: 1:20 SHEET 1 OF 1