



TITLE  
**PW712.INS-2 (AG)**

DRAWN BY J. Ellison DATE 06/04/2022

CUSTOMER CUSTOMER

**NOTE:**  
All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

DESCRIPTION:  
PW712-AG Two piece cold water storage tank suitable for AG/AF Air gaps

A4 ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
16/12/2021	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1090 x 860 x 760mm
EXTERNAL DIMENSIONS	1240 x 1010 x 796mm
NOM. CAPACITY	712 Litres
DRY WEIGHT	45 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

SCALE: 1:20 SHEET 1 OF 1