



TITLE
PW2001.INS-2 (AG)

DRAWN BY
J. Ellison

DATE
06/04/2022

CUSTOMER
CUSTOMER

NOTE:
All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm
UNLESS OTHERWISE STATED

DESCRIPTION:
PW2001-AG Two piece cold water storage tank suitable for AG/AF Air gaps

A4

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
14/12/2021	A	FIRST ISSUE

TANK SPECIFICATION :

INTERNAL DIMENSIONS	1000 x 1000 x 2000mm
EXTERNAL DIMENSIONS	1180 x 1180 x 2093mm
NOM. CAPACITY	2000 Litres
DRY WEIGHT	150 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

TANKS DIRECT

SCALE: 1:35

SHEET 1 OF 1