



TITLE		NOTE: All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
PW4001.INS (AB)		
DRAWN BY	DATE	
J. Ellison	06/04/2022	
CUSTOMER	A4	
CUSTOMER	ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	

DESCRIPTION:		
PW4001-AB One piece cold water storage tank suitable for AB Air gaps		
ALL DIMENSIONS IN MM - DO NOT SCALE		

DATE	VERSION	NOTES
15/12/2021	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	2000 x 1000 x 2000mm
EXTERNAL DIMENSIONS	2202 x 1202 x 2325mm
NOM. CAPACITY	4000 Litres
DRY WEIGHT	300 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

SCALE: 1:40	SHEET 1 OF 1
-------------	--------------