

## S Series

### Pond Pumps



Model	Flow		Height max		Hose Diameter inches	Weight kg	Dimensions mm L x W x H	Power W	
	l/hour	gph	meters	feet				110V	240V
S-4000	3600	951	2.6	8.5	1" 1/4" 1 1/2"	3.5	359 x 135 x 162	55	45
S-5000	4800	1268	2.2	7.2	1 1/4" 1 1/2"	3.6	359 x 135 x 162	67	60
S-6000	6100	1611	2.1	6.9	1 1/4" 1 1/2"	3.6	359 x 135 x 162	n/a	65
S-8000	7800	2061	3.5	11.4	1" 1/4" 1 1/2"	3.7	359 x 135 x 162	93	80
S-9000	9500	2510	3.8	12.4	1" 1/4" 1 1/2"	3.7	359 x 135 x 162	n/a	105
S-10000	10000	2642	4.2	13.8	1" 1/4" 1 1/2"	3.9	359 x 135 x 162	147	135
S-12000	11300	2985	4.2	13.8	1" 1/4" 1 1/2"	4.0	359 x 135 x 162	165	155
S-15000	15200	4015	4.9	16.1	1 1/2" 2"	4.8	402 x 165 x 189	215	210
S-18000	17350	4583	6.1	20.0	1 1/2" 2"	5.2	402 x 165 x 189	285	285
S-20000	19100	5046	6.3	20.7	1 1/2" 2"	5.3	402 x 165 x 189	278	318
S-23000	23000	6076	7.8	25.6	1 1/2" 2"	5.3	402 x 165 x 189	520	520
S-25000	25000	6604	8.2	26.9	1 1/2" 2"	5.8	402 x 165 x 189	593	620

#### Performance

3600 to 25000 l/hour  
 951 to 6604 gph

#### Characteristics

High quality aluminium and ceramic shaft ensure long life even in continuous duty

Can be used submersed or inline

Vortex impeller

Can pump suspended solids up to 6mm

Integral thermal cutout

Ideal for pond aeration, filter systems or water features

Multi year warranty

#### Connections

Connector options: 1", 1 1/4", 1 1/2" OD

Supplied with 10 metre lead and plug

#### Accessories in the box

S-4000 - S-12000  
 Elbow connector, horizontal connectors of 1", 1 1/4", and 1 1/2" OD

S-15000 - S25000  
 Elbow connector, horizontal connectors of 1 1/2" and 2" OD, 360° ball joint, stepped adapter

