



TITLE PW.2x1x1.TIF.AG	
DRAWN BY C.MORRIS	DATE 01/02/2023
CUSTOMER CUSTOMER	

NOTE: Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.	A4
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	

DESCRIPTION: PW.2x1x1.TIF Sectional cold water storage tank c/w access manway to provide an AG Airgap	ALL DIMENSIONS IN MM - DO NOT SCALE
--	-------------------------------------

DATE	VERSION	NOTES
23/01/2023	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	2150 x 1150 x 1150mm
EXTERNAL DIMENSIONS	2224 x 1224 x 1351mm
NOM. CAPACITY	2843 Litres
INSULATION THICKNESS	38mm
MATERIAL	Hot press moulded GRP

	SCALE:1:25	SHEET 1 OF 1
--	------------	--------------