



TITLE PW.3x1x2.TIF.AB	
DRAWN BY J. Ellison	DATE 01/02/2023
CUSTOMER CUSTOMER	

NOTE: Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.	A4
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	

DESCRIPTION: PW.3x1x2.TIF Sectional cold water storage tank c/w raised float valve housing to provide an AB Air gap	ALL DIMENSIONS IN MM - DO NOT SCALE
--	-------------------------------------

DATE	VERSION	NOTES
27/01/2023	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	3150 x 1150 x 2150mm
EXTERNAL DIMENSIONS	3224 x 1224 x 2710mm
NOM. CAPACITY	7788 Litres
INSULATION THICKNESS	38mm
MATERIAL	Hot press moulded GRP

	SCALE:1:40	SHEET 1 OF 1
--	------------	--------------