

Klargester BioDisc® Domestic Sewage Treatment Plant



^{*} Dimensions illustrated here are applicable to the BA and BB models only.

Choosing the right sewage treatment plant for your home with Klargester

Klargester provides relevant advice and support throughout the wastewater treatment purchasing process based on our in-depth local knowledge and expertise. We offer comprehensive free site visits, professional installation options (optional extra) and aftersales care through our national network of accredited installers and engineers.

BioDisc is Third Party Tested to EN 12566-3 (GB & NI) and SR66:2025 (IE)

I'm a homeowner - what do I need to consider before choosing my treatment plant? The Klargester BioDisc sewage treatment system is available to suit all types of domestic applications, catering for single and multi-house properties. BioDisc is engineered to treat wastewater to a very high standard and offers affordable lifetime costs compared to other treatment processes.

Our team will guide you through:


- Size of treatment plant required
- Ground conditions around the plant
- Wastewater discharge options
- Invert level options

Why BioDisc®? Product benefits With strict Environment Agency Affordable lifetime Trusted and reliable standards, it's more important running costs performance than ever to choose a sewage treatment plant that delivers peace of mind with reliable Odour free Silent Operation treatment of wastewater. At a recent site, our team concluded that the The Klargester BioDisc is built on domestic BioDisc has the same level of noise as the average ambient background noise outside (between 40-55 decibels).* the back of 70 years' experience and offers the following benefits: an air pump (used in an 'aerated' system) which neans minimal odour bein released. This is verified by an independent odour Typical aerated system coffee grinder machine Domestic BioDisc Decibel equivalent to * This is a representative figure based on a Large BioDisc plant. Register your guarantee online at kingspan.co.uk/klargesterguarantee to arrange your

service and enjoy an extended seven year guarantee period.**

** For BA and BB BioDisc models only, when registered online - terms and conditions apply. Visit: kingspan.com/gb/en-gb/products/wastewater-management/warranty-terms

How it works



Primary settlement tank

Wastewater and sewage flows into the primary settlement tank where the large solids are retained for future removal.



First stage biological treatment

The liquor and fine solids then flow into the Biological Treatment Zone 1 where the first stage of treatment occurs.



Second stage biological treatment

The liquor is then fed forward at a controlled rate into Biological Treatment Zone 2 for further treatment.





Final settlement tank

The clean liquid passes into the final settlement tank where it can be discharged to ground or water course.



Control panel and beacon featuring alarm* and digital display to signal that your system is working optimally (beacon and alarm optional extras).

SmartServ Pro

Ask us about our SmartServ Pro remote monitoring solution (optional extra). With early fault detection, SmartServ Pro lets you know when your system needs serviced, giving you peace of mind. Find out more at helpingyou@kingspan.com



Integrated Pump System also available (for pumped systems only). Our technical team will guide you through the best options for your site.

 $Book\ your\ free\ site\ visit\ from\ our\ in-house\ Klargester\ team\ at\ klargester@kingspan.com\ or\ visit\ \textbf{klargester.co.uk}$







Technical Specification

| Unit Reference | BA | BAx | ВВ | ВС |
|-----------------------------------|----------------|----------------|----------------|-----------|
| Population Equivalent (Std Flow) | 6 | 9 | 12 | 18 |
| Maximum Daily BOD (kg) | 0.36 | 0.54 | 0.72 | 1.08 |
| Maximum Daily Flow (m3) | 1.2 | 1.8 | 2.4 | 3.6 |
| Ø/Width (mm) | 1995 | 1996 | 1995 | 2450 |
| Length (mm) | - | - | - | - |
| Inlet Invert depth (mm) | 450/750/1250 | 450/750/1251 | 450/750/1250 | 600/1100 |
| Depth Below Inlet Invert (mm) | 1400 | 1400 | 1400 | 1820 |
| Outlet Invert Depth (mm) | 1315 | 1315 | 1315 | 1735 |
| Overall Height (mm) | 2160/2460/2960 | 2160/2460/2960 | 2160/2460/2960 | 2825/3325 |
| Height to Rim of Cover (mm) | 1945/2245/2745 | 1945/2245/2745 | 1945/2245/2745 | 2485/2985 |
| Empty Weight (kg) | 310/325/380 | 310/325/380 | 335/350/405 | 650/750 |
| Standard Power Supply | 1 phase | 1 phase | 1 phase | 1 phase |
| Motor Rating - 1 Phase (Watts) | 50 | 50 | 50 | 75 |
| Full Load Current 1 Phase (amps) | 0.51 | 0.51 | 0.51 | 1,1 |
| Optional Power Supply | 3 phase | 3 phase | 3 phase | 3 phase |
| Motor Rating - 3 Phase (Watts) | N/A | N/A | N/A | 90 |
| Full Load Current 3 Phase (amps) | N/A | N/A | N/A | 0.38 |
| Sludge Return Pump Rating (watts) | 250 | 250 | 250 | 250 |

Invert level options

Three standard drain invert level options are available from stock to match the site topography and where applicable, minimise the excavation depth. The BA, BB and BA-X models are available with an integral pump to move the effluent from the point of treatment, if site level demands.

Environment Agency regulations

As an off-mains homeowner, you must comply with the General Binding Rules by ensuring your treatment system is maintained properly and does not cause pollution. These rules state that you must arrange

regular maintenance for your system, via a trusted service provider. Kingspan Service can help with servicing and alarm packages – email helpingyou@kingspan.

Protect your investment with our Service and Maintenance Plans

We recommend that you service your BioDisc sewage treatment plant **once a year**. Under Environment Agency regulations, it's now your responsibility to ensure smooth running of your plant.

Our in-house Service department offer a range of service packages including Gold, Silver and Bronze

to cater for all homeowners' needs.

To find out more about how you could benefit from a tailored service package from Kingspan, call us on +44 (0)28 3026 6799 (NI) or 0818 544 500 (ROI) or email helpingyou@kingspan.com

For further technical information & videos on the BioDisc treatment plant visit our website at **klargester.co.uk**

Contact Details

UK

Kingspan Water & Energy Ltd.

College Road North Aston Clinton | Aylesbury Buckinghamshire | HP22 5EW

T: +44 (0) 1296 633 033 F: +44 (0) 1296 633 001 E: klargester@kingspan.com www.klargester.co.uk

Kingspan Water & Energy Ltd.

Service Office Details: 180 Gilford Road Portadown | BT63 5LF

04/2025 v5 5010.01

T: NI: +44 (0)28 3836 4600 ROI: 0818 543 500

E: helpingyou@kingspan.com www.kingspanservice.com

