

UNDERGROUND GRP SPEL TANK

PLEASE COMPLETE – EMAIL TO sales@tanks-direct.co.uk or FAX 0333 222 3858

Price on site is based on basic spec of: 2 x 110mm spigots, 1 x 600mm diam. access shaft (300mm high). Non Potable.

Customer Name	
Company Name	
Telephone Number	
Address.....Street	
Address.....Town	
Address.....County	
Address.....POST CODE	
Delivery Address.....Street	
Delivery Address.....Town	
Delivery Address.....County	
Delivery Address.POST CODE	
Delivery Notes	
What is the tank for?	
Potable Drinking Water?	
Capacity Required?	
Product Code?	
Inlet Options: Std size is 110mm open ended spigot – other sizes are available	
Outlet Options: Std size is 110mm open ended spigot - other sizes are available (160mm generally 300 Series)	
Access Shaft Standard: 600mm diam x 300mm high 750mm (300 Series)	
Inlet / outlet location see attached images	
Breather required?	
Lid – Only option is cover & frame, 600 x 600 Ductile iron, double triangular design, Class D400 Model MC1605/Cover600X600.D400 – sits above tank – does not sit on shaft - £105 +vat	
Surround eg: Pea gravel/concrete?	
Extension Neck required?	
Water table depth?	
Can they off load?	
HIAB Required?	
Artic Access?	
Other	