

CE

Powertank Compact: 125ltr

The Powertank Compact has been specifically designed for smaller properties with low water pressure and flow and where space is at a premium i.e. apartments, cottages, townhouses. Fitting into the space of a standard kitchen unit, the Powertank Compact is a similar size to a washing machine so can be hidden away behind a cupboard door. The electronic controller automatically starts and stops the pump when a drop in pressure is sensed i.e. a tap is opened and closed.

Key Features

- Non-corrosive holding tank (WRAS approved material)
- Pre-fitted WRAS approved fill valve
- · Integral overflow weir
- Minimal installation required
- Adjustable digital display flow controller
- Dry run protection with auto restart (time delay)




Range Options

Model
125ltr Compact Fixed Speed
125ltr Compact Variable Speed
125ltr Compact Fixed Speed Auto Tech

System Connections

Connection	Size
Inlet	½"BSP
Outlet	1"BSP
Overflow	1 ½"
Drain Off	1"BSP



125ltr Compact

	Fixed Speed Option	Variable Speed Option				
Power supply	240 volt, 50Hz	240 volt, 50Hz				
Controller	Presflo 1.5 supplied with 2ltr pressure vessel	Steadypres MT07 supplied with 2ltr pressure vessel				
Current Input	3.4 amp	3 amp				
Mains Power Cable	2 mtr x 1mm2 3 core fitted with 5 amp fuse main plug	2 mtr x 1mm2 3 core fitted with 5 amp fuse main plug				
Tank Weight Empty	27 kg	33 kg				
Tank Weight Full	1ltr = 1 kg plus weight of empty tank	1ltr = 1 kg plus weight of empty tank				
Access Cover Ø	190mm	168mm				

Pump Option	Power		Q l/min		10	20	30	40	50	60	70	80
	kW	HP	Q //min		10	20	30	40	50	60	/0	0 0
Fixed Speed	0.55	0.75	H Metres	42	40	38	34	30	24	18	11.5	5
Variable Speed	0.55	0.75	H Metres	48	46	44.5	42.8	40.5	37.5	33.5	29	23

Please note that we have a policy of continuous product development and specifications may change from those shown

