



2 No 40mm Encapsulated
RHS Steel Bracings

310
300

TITLE		NOTE: All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
PW2726.INS.AG		
DRAWN BY	DATE	
C.MORRIS	27/11/2017	
CUSTOMER	A4	
CUSTOMER	ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	

DESCRIPTION:	PW2726 one piece cold water storage tank suitable for AG/AF Air gap
ALL DIMENSIONS IN MM - DO NOT SCALE	

DATE	VERSION	NOTES
02/10/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1828 x 1220 x 1220mm
EXTERNAL DIMENSIONS	2020 x 1410 x 1313mm
NOM. CAPACITY	2726 Litres
DRY WEIGHT	168
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP



SCALE:1:25 SHEET 1 OF 1