



TITLE	
PW3185.INS.AG	
DRAWN BY	DATE
C.MORRIS	27/11/2017
CUSTOMER	
CUSTOMER	

**NOTE:**  
All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

**DESCRIPTION:**  
PW3185 one piece cold water storage tank suitable for AG/AF Air gap

DATE	VERSION	NOTES
02/10/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	2440 x 1220 x 1070mm
EXTERNAL DIMENSIONS	2610 x 1410 x 1163mm
NOM. CAPACITY	3185 Litres
DRY WEIGHT	175 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP



SCALE:1:25      SHEET 1 OF 1

D  
C  
B  
A

D  
C  
B  
A

6      5      4      3      2      1

6      5      4      3      2      1