



TITLE		NOTE: All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
PW6001.INS.AG		
DRAWN BY	DATE	
C.MORRIS	27/11/2017	
CUSTOMER		
CUSTOMER		

DESCRIPTION:	
PW6001 one piece cold water storage tank suitable for AG/AF Air gaps	
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	

TANK SPECIFICATION :		
INTERNAL DIMENSIONS	2000 x 2000 x 1500mm	
EXTERNAL DIMENSIONS	2192 x 2192 x 1593mm	
NOM. CAPACITY	6000 Litres	
DRY WEIGHT	350 KG	
INSULATION THICKNESS	25mm	
WRAS CERT. NUMBER	1310072	
MATERIAL	GRP	

DATE	VERSION	NOTES
06/11/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	2000 x 2000 x 1500mm
EXTERNAL DIMENSIONS	2192 x 2192 x 1593mm
NOM. CAPACITY	6000 Litres
DRY WEIGHT	350 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

		SCALE: 1:20	SHEET 1 OF 1
		A4	