



TITLE		<small>NOTE:</small> All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.	DESCRIPTION: PW250 one piece cold water storage tank c/w raised float valve housing to provide an AB Air gap	DATE	VERSION	NOTES
PW250.INS.AB.6				04/10/2017	A	FIRST ISSUE
DRAWN BY	C.MORRIS			DATE	27/11/2017	
CUSTOMER	CUSTOMER	ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	A4	ALL DIMENSIONS IN MM - DO NOT SCALE		

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1000 x 500 x 500mm
EXTERNAL DIMENSIONS	1180 x 680 x 810mm
NOM. CAPACITY	250 Litres
DRY WEIGHT	20 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP



SCALE:1:20 SHEET 1 OF 1