



OUTER TANK: Corrosion free, robust Polyethylene tank.

INNER TANK: Corrosion free, robust Polyethylene inner tank, 20mm insulation fitted to the tank walls, 25mm under floor insulation c/w Base Heating system. 2" filler cap. Contents gauge. Pump Suction Pipe and vented 180mm inspection lid.

FRAME: Galvanised 5mm reinforced steel frame with 5mm protective bottom base plate c/w built in fork sockets on four sides. Four corner lifting eyes. Gas strut assisted secure lockable steel access lid.

STORAGE: Approved to stack 2 high when full and 3 high when empty.

OPTIONAL PUMPS: 110v or 240v On Demand Pump c/w trace heating wire to prevent freezing. All hoses are trace wire heated and insulated to prevent freezing c/w thermostatically controlled unit. All mounted in a bolt-on galvanised lockable cabinet.

FINISH: Blue Polyethylene Drinking Water tank approved, as standard. Other colours available. Galvanised frame and lid.

DIMENSIONS: (Approximate)

Width: 1213mm (exc.cabinet)
Length: 1213mm (exc.cabinet)
Height: 1430mm overall (exc.cabinet)
Laden Weight: 1300kg

Cabinet Width: 300mm
Cabinet Length: 910mm
Cabinet Height: 450mm
Unladen Weight: 300kg

