



**CHASSIS:** Constructed from 80 x 80 RSA. fully welded with a 'T' frame drawbar, all fully hot dipped galvanised. 5mm sheet front mounting plate.

**AXLE/SUSPENSION:** Knott-Avonride 1500kg rubber torsion beam axle fitted with 200 x 50 auto reverse brakes on 4 stud 5 1/2" pcd hubs.

**WHEELS AND TYRES:** 2 no. 175 x 13 x 8 ply tyres on 4 Stud 5 1/2" pcd Rims.

**COUPLING:** Knott-Avonride 2000kg auto reverse coupling fitted with 40mm eye or 50mm Ball, break away cable and spring assisted hand brake lever.

**TANK:** Polyethylene moulded tank elliptical in section, baffled & fitted with a 22" lockable outer hinged manlid covering inner sealed vented manlid. Tank secured to chassis with 2 stainless steel straps. 1 rear tap (2 rear outlets).

**PUMP:** 1" Honda petrol engine driven pump c/w 50ft of 1/2" hose on a hand rewind hose reel, c/w spray nozzle.

**ANCILLARY EQUIPMENT:** Moulded mudguards, mud flaps, front telescopic jockey wheel, Side reflectors, Front reflectors, rear lighting board c/w 13 pin plug and 7 pin adapter.

**OPTIONAL EXTRA:** Rear chevron board with directional arrow & flashing beacons. Alternative pumps & hose reels on request

**FINISH:** Polyethylene tank in choice of yellow, green, blue or red. Galvanised Chassis.

**DIMENSIONS:** (Approximate)

**Width:** 1.5m (61")

**Length:** 3.454m (136")

**Height:** 1.346m (53)

**Laden Max:** 1500kg

**Unladen weight:** 375kg approx

**Towing Height:** (Level) 420mm