



25mm Encapsulated
RHS Steel Bracings

250

TITLE
PW650.INS-2.AG

DRAWN BY C.MORRIS DATE 27/11/2017

CUSTOMER

NOTE:

All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm
UNLESS OTHERWISE STATED

A4

DESCRIPTION:

PW650-2 piece cold water storage tank
suitable for AG/AF Air gap

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
18/09/2017	A	FIRST ISSUE

TANK SPECIFICATION :

INTERNAL DIMENSIONS	1067 x 610 x 1000mm
EXTERNAL DIMENSIONS	1255 x 805 x 1039mm
NOM. CAPACITY	650 Litres
DRY WEIGHT	43 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP



SCALE:1:15

SHEET 1 OF 1