







3D Image
Scale 1:35



TITLE
PW7500.INS-2.AG

DRAWN BY **C.MORRIS** DATE **28/11/2017**

CUSTOMER **CUSTOMER**

NOTE:
All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

DESCRIPTION:
PW7500-2 piece cold water storage tank suitable for AG/AF Air gaps

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
06/11/2017	A	FIRST ISSUE

TANK SPECIFICATION :

INTERNAL DIMENSIONS	2500 x 2000 x 1500mm
EXTERNAL DIMENSIONS	2692 x 2192 x 1593mm
NOM. CAPACITY	7500 Litres
DRY WEIGHT	380 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP



SCALE:1:30 SHEET 1 OF 1

D
C
B
A

D
C
B
A

6 5 4 3 2 1

6 5 4 3 2 1