



**CHASSIS:** Constructed from 5mm pressed steel section fully welded with a front standing plate and 100 x 50 RSC 'A' frame drawbar.

**AXLE/SUSPENSION:** Single Knott-Avonride 3000kg torsion beam axle fitted with 300 x 60 auto reverse brakes.

**WHEELS AND TYRES:** 2 no. 235 /85 x 16 x 12 ply radial tyres on 5 stud 61/2" pcd rims.

**COUPLING:** Knott-Avonride 3000kg capacity posibrake over run auto reverse coupling c/w breakaway cable, spring assisted handbrake lever, fitted with 40mm eye or 50mm ball.

**TANK:** Polyethylene moulded tank, elliptical in section, with internal anti surge baffle & fitted with a 22" lockable outer hinged manlid cover, inner sealed vented manlid. 2" front draw off, 2 rear outlet connections. Tank secured to chassis with 2 stainless steel straps.

**ANCILLARY EQUIPMENT:** moulded mudguards, mud flaps, front telescopic jockey wheel, Side reflectors, & front markers, full road lighting c/w 13 pin plug and 7 pin adapter.

**PUMP:** Optional on request.

**FINISH:** Polyethylene tank in yellow, green, red or blue drinking water only. Chassis galvanised as standard. Primer and two top coats in BS colour optional on request.

**DIMENSIONS:** (approximate)

**Width:** 1.982m (78")

**Length:** 3.530m (139")

**Height:** 1.600m (63")

**Laden weight:** 2800kg

**Unladen weight:** 600kg approx

**Towing height:** (level) 480mm