



CHASSIS: Constructed from 5mm pressed steel section fully welded with a 100 x 50 RSC 'A' frame drawbar and front standing plate.

AXLE/SUSPENSION: Twin Knott-Avonride 1500kg torsion beam axles fitted with 200 x 50 Auto reverse brakes.

WHEELS AND TYRES: 4 No. 175 /13 x 8 Ply tyres on 4 stud rims.

COUPLING: Knott-Avonride 3000kg auto reverse coupling fitted with either a choice of 40mm eye or 50mm ball, break away cable and spring assisted hand brake lever.

TANK: Polyethylene, elliptical in section with internal anti surge baffle, 2" front draw off, 2 rear outlet connections, fitted with a 22" lockable outer hinged manlid cover, inner sealed vented manlid. Tank secured to chassis with 2 stainless steel straps.

ANCILLARY EQUIPMENT: moulded tandem mudguards, heavy duty jockey wheel, c/w side reflectors, front markers, rear lighting board c/w 13 pin plug and 7 pin adapter.

FINISH: Poly tank in yellow, green, red or blue. Drinking water blue tank only. Chassis galvanised as standard , optional primer and two top coats in BS colour available.

DIMENSIONS: (Approximate)

Width: 1.790m (70 1/2")

Length: 3.535m (139")

Height: 1.550m (61")

Variations in towing height: -25mm + 100mm

Unladen Weight: 500kg approx

Laden Max: 3000kg

Towing Height:(Level) 394mm