

Single and Double Door Kiosks

Our kiosks are available in both single door, and double door options to all you maximum flexibility when installing control panels, alarms, and other equipment.

Each kiosk is manufactured from 2mm Zintec sheet steel to BS6687-1968 (Chromate washed - substrate BS1449-2.5 microns), the kiosks are press formed and welded construction to IP55 of BS5490 to give good earth continuity.

Our Manufacturing Process

- ▶ Degrease and clean to remove dust
- ▶ One coat of two pack etching primer
- ▶ Air-dry for one hour
- ▶ Two coats of pure polyester powder paint to give maximum dry film thickness of 50 microns
- ▶ Stove at 180 degrees for 45 minutes

	HEIGHT	WIDTH	DEPTH
SINGLE DOOR KIOSK	1250mm	750mm	450mm
DOUBLE DOOR KIOSK	1250mm	1250mm	450mm

Kiosk Included Components

- ▶ Kiosk lifting brackets
- ▶ Wooden Backboard
- ▶ 14mm floor fittings
- ▶ Door stays
- ▶ Flush 17mm triangular locks
- ▶ Door brackets to facilitate the fitting of Yale locks
- ▶ Full height unistruts at the rear of each section
- ▶ internal hinges
- ▶ Earthing points

Optional Extras

- ▶ Ventilation Covers
- ▶ Cat-Flap for generator connection
- ▶ Anti-condensation heater and thermostat
- ▶ Plinth

