

SPECIFICATION FOR DAMMIT® MATS



	4000/X	4010/X	4020/X	4030/X
Size	65 x 45 x 1.4 cm	45 x 45 x 1.4 cm	22.5 x 20 x 1.4 cm	65 x 15 x 1.4 cm
Pack Quantity	2	2	12	6
Pack Wt	11.8 kg	8.3 kg	11.8 kg	11.9 kg
Pack Size	67 x 48 x 6 cm	48 x 48 x 6 cm	67 x 48 x 6 cm	67 x 48 x 6 cm

Composition: A water-based gel containing a food-grade clay, a recycled polymeric reinforcing agent and a

low toxicity freezing point depressant.

How to use: Dammit clay drain mats are easy to use and quick to deploy:

Step 1: Remove mat from the protective bag Step 2: Peel off plastic sheet from underside Step 3: Place mat on drain sticky side down

Step 4: Tread on mat to ensure complete contact with drain

Properties: Highly flexible and strong (Non-woven reinforcing layer)

Excellent adhesion to all surfaces

Usable down to -20°C

Pack Type: Mats are supplied wrapped in thin polythene film inside a sealed polythene bag, with tags for

easy opening. The bags are packed in heavy-duty cardboard cartons for storage and

shipping.

Compatibility: Good resistance to water, oil and a wide range of chemicals over short-term exposure (1-5

hrs), and in many cases for at least 24 hrs. Full details available on request.

Shelf Life: 3 years (In sealed bag).

Safety Data: Refer to our Safety Data Sheet.

Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.



01643 703358 www.tanks-direct.co.uk sales@tanks-direct.co.uk