

MINIBREAK CAT 5 TANK AND BOOSTER SET



MiniBREAK

Single-pump, compact, easy-to-install unit to provide fluid category 5 backflow protection.

PRODUCT OVERVIEW

- LDPE and stainless steel housing
- 18-litre break tank
- Suitable for wall or floor mounting

Key Features







Specification

The MiniBREAK single pump packaged tank and booster set has been designed to be compact and provide fluid cat 5 backflow protection via an 'AB' air gap. It complies with the water supply (water fittings) regulations 1999 and comes as a complete package in an enclosed cabinet suitable for wall or floor mounting.

The pump control is provided by a well-proven intuitive controller that will start the pump at falling pressure and stop the pump when flow ceases. The control unit also provides low water protection.

PRODUCT OVERVIEW


- Volt-free contact for pump running
- IP65-rated controller
- Low-water protection device
- Wall or floor mountable
- Single phase

APPLICATIONS

- Wash down in bin stores
- Dentist's rinsing equipment
- Laboratory water supplies
- Single hosepipe supplies
- Any application where cat 5 protection is required mortuaries, abattoirs, zoos, healthcare premises, etc.

OPTIONS

- Frost protection kit



RANGE PERFORMANCE

Number of pumps	1
Typical duty	0.2 l/s @ 2.5 bar 0.3 l/s @ 1.8 bar 0.4 l/s @ 1.2 bar
Break tank capacity	23 litres
Noise data	Motor at $< 70 \text{ LpA}$ (dB +/-2) $^{\circ}$

*More specific details available on request.

MATERIAL SPECIFICATION

Housing	LDPE
Pump body	PPE and brass
Pipework and fittings	Copper, brass, stainless steel

MINIBREAK™ MODEL

MB1-38M-S	MiniBREAK cat 5 booster system
MB1-38M-FP	MiniBREAK frost protection kit

VOLT-FREE CONTACTS PUMP RUNNING

Both open and closed volt-free contacts are available, which indicate if the pump is running. See the appropriate drawing for volt-free contact wiring configurations.

RECOMMENDED CLEARANCE FOR ACCESS

USEABLE TANK VOLUME: - 12.5L


WALL MOUNTING INSTRUCTIONS:


M8 WALL FIXING SCREW BOLTS ALONG WITH PENNY WASHERS
TO BE UTILISED FOR SECURE WALL MOUNTING.

THE PRODUCT WEIGHS 45 KG, SO ENSURE THE DRILLED HOLES ARE SUFFICIENTLY DEEP TO WITHSTAND THE PULL-OUT FORCE. FAILURE TO DO SO MAY LEAD TO IMPROPER INSTALLATION.

MB1 Series

SINGLE PUMP CURVES







Scan to get your copy of the Big Red Book, or visit dutypoint.com/big-red-book



Let's talk about your cat 5 requirements

01452 300110 ENQUIRIES@DUTYPOINT.COM DUTYPOINT.COM